

DTH-20CT (DVI-D - HDMI Cable Tester)



Power supply : 1. USB Power cable 2. Battery-3*3A
3. AC Adapter (option)



Features & Specification

- DC 5V Power required
- With DVI-F & HDMI-F Connectors
- LED display test result
- Test cable Open & Short
- Open / Short : LED NO Light
- Easy to test
- With 3 colors LED appeared
- Compact size
- Housing : Plastic,
- Weight : 55g
- Dimensions (L*W*H) : 47 * 45 * 21 (mm)
- With 5V / 3.5mm power jack (Inner + / Outer -)
- With 5V USB power cable
- Power jack :Center pin / 1.3mm

Test - Table

- Pin Assignment :

DVI-D-F	HDMI-F	Signal	Text	LED-Color
Pin 1	Pin 3	D2-	RX2	Red *
Pin 2	Pin 1	D2+	RX2	Green *
Pin 6	Pin 15	DDC-C	CK	Green
Pin 7	Pin 16	DDC-D	DA	Green
Pin 9	Pin 6	D1-	RX1	Red *
Pin 10	Pin 4	D1+	RX1	Green *
Pin 14	Pin 18	+5V	5V	Red
Pin 8	Pin 14	HEAC+	HPD	Green *
Pin 16	Pin 19	HPD/HEAC-	HPD	Red *
Pin 17	Pin 9	D0-	RX0	Red *
Pin 18	Pin 7	D0+	RX0	Green *
Pin 23	Pin 10	CLK+	RXC	Green *
Pin 24	Pin 12	CLK-	RXC	Red *
CableShield		Shield	VH-CEC	Green
Pin 3/11/19/22	Pin 2/5/8/11	GND1	D0/D1/D2/CLK Shield	
Pin 15	Pin 17	GND2	GND	
DVI - Pin 4/5/12/13/20/21/C1~C5		NC		

- * Double color LED